



PortaSens III GAS LEAK DETECTOR

PortaSens III

MODEL D16 GAS DETECTOR

Locating the source of gas leaks can be a challenge, especially in plant areas with multiple potential leak sources. Ammonia refrigeration piping, ozone generator skids, and hazardous gas piping systems are just a few of the applications where identifying exact leak sites is difficult.

ATI's new PortaSens III portable leak detector (Model D16) is ideal for locating leak sources or simply for measuring gas concentrations in the workplace. With a built-in sampling pump and inlet wand, sample is drawn from precise locations where leaks may occur. Areas around valve packing, flanges, compression fittings and other system components are easily checked to find the higher gas levels that exist near the leak site.

The PortaSens III is physically similar to its predecessor, the PortaSens II which has been in service for the past 15 years. The internals of the instrument have been completely redesigned with a modern USB computer interface, a color touch-screen display, and improved pump control. As with the original, the D16 detector has the ability to measure a wide variety of gases by simply inserting the appropriate sensor for that gas. The D16 can use any of over 60 different sensor modules, providing nearly unmatched flexibility. Sensors can be changed quickly and easily without the need for calibration.

Sensors used in the PortaSens III are ATI's H-Series smart sensor modules. Each sensor module is actually a sensor, amplifier, and memory module in one compact package. Because of this design, sensor modules can be calibrated independently and simply plugged into any detector for immediate use.

When installed in a detector, calibration data is loaded into the microprocessor so that no adjustments are needed. The result is that a detector can, for example, go from phosgene measurement to ammonia measurement in less than one minute.

FEATURES

- Interchangeable "Smart Sensors" for gas flexibility
- NEW IR sensors for methane & carbon dioxide
- Internal sample pump and external sampling wand
- One-hand pistol grip design
- NiMH "D" cell rechargeable battery or alkaline cell
- Easy to read back-lit color graphics LCD
- Instantaneous and timed-sampling modes of operation
- Visual and Audible alarms
- Internal 4 Gb data-logger with USB output





SMART SENSORS

The basic PortaSens II detector does not include sensor modules. Because the D16 is designed to accept any ATI smart sensor module, you must select one or more sensors from the list below. Each sensor module is factory calibrated at the time of shipment and is ready to use by plugging it into the receptacle in the D16 manifold. Each module can be used for logging data over minimum and maximum ranges indicated.



AVAILABLE SENSORS

00-1000	Br ₂ , 0-1/5 ppm	Bromine	00-1025	AsH ₃ , 0-10/200 ppm	
00-1001	Br ₂ , 0-5/200 ppm		00-1026	B ₂ H ₆ , 0-500/2000 ppb	Diborane
00-1002	Cl ₂ , 0-1/5 ppm	Chlorine	00-1027	B ₂ H ₆ , 0-10/200 ppm	
00-1003	Cl ₂ , 0-5/200 ppm		00-1028	GeH ₄ , 0-500/2000 ppb	Germane
00-1004	ClO ₂ , 0-1/5 ppm	Chlorine Dioxide	00-1029	GeH ₄ , 0-10/200 ppm	
00-1005	ClO ₂ , 0-5/200 ppm		00-1030	H ₂ Se, 0-500/2000 ppb	Hydrogen Selenide
00-1359	ClO ₂ , 200/1000 ppm		00-1031	H ₂ Se, 0-10/200 ppm	
00-1425	ClO ₂ , 0-1/5 ppm (low Cl ₂)		00-1032	PH ₃ , 0-500/2000 ppb	Phosphine
00-1006	F ₂ , 0-1/5 ppm	Fluorine	00-1033	PH ₃ , 0-10/200 ppm	
00-1007	F ₂ , 0-5/200		00-1034	PH ₃ , 0-200/2000 ppm	
00-1008	O ₃ , 0-1/5 ppm	Ozone	00-1035	SiH ₄ , 0-10/200 ppm	Silane
00-1009	O ₃ , 0-5/200 ppm		00-1036	I ₂ , 0-1/5 ppm	Iodine
00-1358	O ₃ , 200/1000 ppm		00-1037	I ₂ , 0-5/200 ppm	
00-1163	O ₃ , 500/2000 ppb		00-1038	Acid Gas, 0-10/200 ppm	Acid Gases
00-1010	NH ₃ , 0-50/500 ppm	Ammonia	00-1039	ETO, 0-20/200 ppm	Ethylene Oxide
00-1011	NH ₃ , 0-500/2000 ppm		00-1040	HCOH, 0-20/200 ppm	Formaldehyde
00-1012	CO, 0-50/1000 ppm	Carbon Monoxide	00-1349	HCOH, 500/2000 ppm	
00-1013	H ₂ , 0-1/10%	Hydrogen	00-1042	H ₂ O ₂ , 0-10/100 ppm	Hydrogen Peroxide
00-1041	H ₂ , 0-500/2000 ppm		00-1169	H ₂ O ₂ , 200/2000 ppm	
00-1014	O ₂ , 0-5/25%	Oxygen	00-1043	Alcohol, 0-50/500 ppm	Alcohol
00-1015	COCl ₂ , 0-1/5 ppm	Phosgene	00-1044	Alcohol, 0-500/2000 ppm	
00-1016	COCl ₂ , 0-5/100 ppm		00-1057	C ₂ H ₂ , 0-200/2000 ppm	Acetylene
00-1017	HCl, 0-10/200 ppm	Hydrogen Chloride	00-1181	NO _x , 0-50/500 ppm	NOX
00-1018	HCN, 0-10/200 ppm	Hydrogen Cyanide	00-1450	DMA, 100/200 ppm	Dimethylamine (DMA)
00-1019	HF, 0-10/200 ppm	Hydrogen Fluoride	00-1455	HBr, 10/200 ppm	Hydrogen Bromide
00-1020	H ₂ S, 0-10/200 ppm	Hydrogen Sulfide	00-1516	HC Sensor – Consult Factory	
00-1469	H ₂ S, 200/1000 ppm		00-1045	CH ₃ COOH, 100/500 ppm	Acetic Acid
00-1021	NO, 0-50/500 ppm	Nitric Oxide	00-1704	PAA Vapor, 1/5 ppm	PAA Vapor Sensor
00-1022	NO ₂ , 0-10/200 ppm	Nitrogen Dioxide	00-1705	PAA Vapor, 10/100 ppm	
00-1023	SO ₂ , 0-10/500 ppm	Sulfur Dioxide	00-1883	IR CH ₄ , 0-20/100% LEL	IR CH4 Sensor (combustible gas)
00-1024	AsH ₃ , 0-500/2000 ppb	Arsine	00-1886	IR CO ₂ , 0-0.2/1.5%	IR CO2 Sensor

Notes:

1. X/XX for each sensor indicates minimum and maximum data logging ranges for that sensor.
2. 00-1883 LEL CH₄ sensor also responds to many other hydrocarbons. Response to other hydrocarbons is not 1:1 with CH₄.

PortaSens III Gas Detectors are supplied in a padded carrying case for easy storage and transport. An extra battery is provided plus space for up to two sensor keepers which means up to 8 extra sensors ready for immediate use.




The following components are standard.

- PortaSens III Gas Detector
- Spare Filters
- 10" Teflon Lined Sampling Wand
- Flowmeter
- USB Cable
- Spare NiMH "D" Cell Battery
- NiMH Battery Charger
- Sensor Keeper
- Calibration "T" Fitting

ORDERING INFORMATION

#00-1876 MODEL D16 PortaSens III

SPECIFICATIONS

Range:	Dependent on sensor module used
Display:	Backlit, touch-sensitive color graphics LCD
Accuracy:	Sensor dependent but generally $\pm 5\%$ of value (limited by cal. gas)
Sensitivity:	Typically 0.1-1% of sensor module range
Output:	USB transfer of stored gas values
Memory:	4 Gb (millions of data points)
Storage Interval:	Programmable from 1 minute to 60 minutes
CE	2014/35/EU – Low voltage directive 2014/30/EU – Electromagnetic compatibility
Alarms:	Three concentration alarms (caution, warning, and danger with adjustable setpoints). Low flow and low battery alarms displayed on LCD & indicated by audible beeper
Power:	Rechargeable NiMH D cell battery runs about 10 hours continuously. Two D cells supplied with unit. Alkaline D cell battery may also be used.
Charger:	2-Cell Charger, 100-240 VAC input
Operating Temp.:	-25° to +55°C
Humidity:	0-95% Non-condensing
Detector Material:	Glass Filled Polycarbonate
Size:	3.5"(W) x 9"(H) x 5.5"(D) 89mm x 229mm x 140mm
Shipping Weight :	7 lbs. (3.2 Kg.)
Environmental	 RoHS Compliant

Visit Us on the Web: www.analyticaltechnology.com

Analytical Technology, Inc.
6 Iron Bridge Drive
Collegeville, PA 19426
Phone 610.917.0991
Toll-Free 800.959.0299
Fax 610.917.0992
Email sales@analyticaltechnology.com

Analytical Technology
Unit 1 & 2 - Gatehead Business Park
Delph New Road, Delph
Saddleworth OL3 5DE
Phone 01457 873 318
Fax 01457 874 468
Email sales@atiuk.com

Represented by: