

5ELR Aluminium Cylinders

Product offering

The 5ELR is a globally approved aluminium cylinder. The 625 litres nominal gas capacity means the cylinder is ideal when larger volumes of gas are required. The cylinder can be supplied with a range of CGA valves designed to meet your specific needs. The cylinder can be filled with non-reactive gases.



| Characteristic | | | | |
|----------------|------------|--------------------|--|------------------------|
| | Contents | Service Pressure | Dimensions | Weight (full pressure) |
| 5ELR | 625 liters | 139 bar (2016 psi) | 734 mm x 111 mm (w/valve) (28.9" x 4.4") | 3.95 kg (8.7 lb) |

| Specifications | | | | |
|----------------|-----------|------------------------------------|---|---|
| | Approvals | Type | Cylinder Valve | Recommended Equipment |
| 5ELR | Global | Refillable Non Reactive Gases Only | CGA Type. Connection to cylinders varies with gas mixtures required | Most commonly used regulators include 1000 Series, DFR 2003, or 718 with CGA connection.. |



Contact Details

Americas

Global Headquarters

Houston, TX, USA
+1 713 624 8000

Customer Service and Manufacturing Facility

Cambridge, MD, USA
+1 800 638 1197

Europe, Middle East & Africa

Customer Service, Sales and Manufacturing Facility

Stoke-on-Trent, United Kingdom
+44 1782 566897

Middle East Sales

Dubai, UAE
+971 56 131 2346

South East Asia & Australia

Customer Service and Distribution

Singapore
+65 62653788

China

Customer Service and Distribution

Shanghai
+86 21 6090 3711

info@calgaz.com

www.calgaz.com

ANSAC

ANSAC TECHNOLOGY (S) PTE LTD

35, Marsiling Industrial Estate Road 3,
#02-01 Singapore 739257

T: (65) 6368 0225 F: (65) 6368 8023

E: sales@ansac-tech.com.sg | www.ansac-tech.com.sg