

# 6D/6DM Steel Cylinders

## Product offering

The 6D and 6DM are globally approved steel cylinders. These cylinders are ideally suited for non reactive gas use. In addition steel cylinders are often specified for use in Mines and other explosive atmospheres (please check regulations). The 6D cylinder holds 103 litres nominal gas capacity and the 6DM being more compact 58 litres of gas. The small lightweight cylinders are easy to carry around. Both cylinders are fitted with a C10 valve.



6D



6DM

Characteristic				
	Contents	Service Pressure	Dimensions	Weight
6D	103 liters	69 bar (1000 psig)	352mm x 83mm (13 7/8" x 3 1/4")	1.4 kg (3 lb)
6DM	58 liters	69 bar (1000 psig)	83mm x 204mm (3.259" x 8.093")	0.9 kg (1.90 lb)

Specifications				
	Approvals	Type	Cylinder Valve	Recommended Equipment
6D	Global	Non-Refillable	C10	Most commonly used regulators include 700 Series, DFR 2000 Series, or 4200 Trigger regulators.
6DM	Global	Non-Refillable	C10	



# Contact Details

## Americas

### Global Headquarters

Houston, TX, USA  
+1 713 624 8000

### Customer Service and Manufacturing Facility

Cambridge, MD, USA  
+1 800 638 1197

## Europe, Middle East & Africa

### Customer Service, Sales and Manufacturing Facility

Stoke-on-Trent, United Kingdom  
+44 1782 566897

### Middle East Sales

Dubai, UAE  
+971 56 131 2346

## South East Asia & Australia

### Customer Service and Distribution

Singapore  
+65 62653788

## China

### Customer Service and Distribution

Shanghai  
+86 21 6090 3711

[info@calgaz.com](mailto:info@calgaz.com)

[www.calgaz.com](http://www.calgaz.com)

**ANSAC**

**ANSAC TECHNOLOGY (S) PTE LTD**

35, Marsiling Industrial Estate Road 3,  
#02-01 Singapore 739257

T: (65) 6368 0225 F: (65) 6368 8023

E: [sales@ansac-tech.com.sg](mailto:sales@ansac-tech.com.sg) | [www.ansac-tech.com.sg](http://www.ansac-tech.com.sg)