

## Miller Falcon Self-Retracting Lifeline

### Description

Miller Falcon, with cable lifeline and high-resistant nylon housing, withstands the harsh rigors of the toughest applications. Pound for pound the strongest, most durable line of self-retracting lifelines on the market.

### Materials

<b>Housing:</b>	High impact-resistant nylon
<b>Lifeline:</b>	7X19, 3/16 in. galvanized or stainless steel cable
<b>Snap Hook:</b>	Galvanized, zinc-plated steel
<b>Carabiner:</b>	Galvanized, zinc-plated steel
<b>Hub:</b>	Stainless steel
<b>Braking Mechanism:</b>	Brass and stainless steel

### Technical

<b>Max. Working Load:</b>	310 lbs. (140.6 kg)
<b>Working Length:</b>	20 ft. (6.1 m) 30 ft. (9.1 m) 50 ft. (15.2 m) 65 ft. (19.8 m)
<b>Max. Arrest Distance:</b>	54 in. (when tested to ANSI Z359.14)
<b>Avg. Arresting Force:</b>	900 lbs. (4 kN) (when tested to ANSI Z359.14)
<b>Max. Peak Arresting Force:</b>	1,800 lbs. (8kN) (when tested to ANSI Z359.14)
<b>Unit Minimum Ultimate Strength:</b>	3,000 lbs. (13.34 kN)

### Certification

Meets all applicable OSHA 1926.502, ANSI A10.32, ANSI Z359.14 Class B and CSA Z259.2.2 requirements.



MP30G-Z7/30FT



MP50G-Z7/50FT

## TECHNICAL DATA

SP525 Rev A/02-17

Model Number	Length	Description	Weight
MP20G-Z7/20FT	20 ft. (6 m)	3/16 in. (5 mm) galvanized cable w/tagline & carabiner	8.9 lb. (4.0 kg)
MP30G-Z7/30FT	30 ft. (9 m)		10.7 lb. (4.9 kg)
MP50G-Z7/50FT	50 ft. (15 m)		10.7 lb. (4.9 kg)
MP65G-Z7/65FT	65 ft. (20 m)		17.1 lb. (7.8 kg)
MP20SS-Z7/20FT	20 ft. (6 m)	3/16 in. (5 mm) stainless steel cable w/tagline & carabiner	8.9 lb. (4.0 kg)
MP30SS-Z7/30FT	30 ft. (9 m)		10.7 lb. (4.9 kg)
MP50SS-Z7/50FT	50 ft. (15 m)		14.8 lb. (6.7 kg)
MP65SS-Z7/65FT	65 ft. (20 m)		17.1 lb. (7.8 kg)

### Limitless Possibilities. Ask the Expert.

Technical Service: 800.873.5242  
[www.millerfallprotection.com](http://www.millerfallprotection.com)

### Honeywell Industrial Safety


900 Douglas Pike  
Smithfield, RI 02917

#### USA

Phone: 800.430.5490  
Fax: 800.322.1330

#### Canada

Phone: 888.212.7233  
Fax: 888.667.8477

 This equipment should only be used after reading and understanding the manufacturer's instructions. Failure to follow instructions could result in serious injury or fatality.