CERTIFICATE OF CONFORMITY

No. CLSBN 080538 0025 Rev. 00

Initial No. -

Certificate Holder:

King's Shoe Manufacturing Pte Ltd

17 Changi Business Park

Central 1

#01-01 Honeywell Building SINGAPORE 486073

SINGAPORE

Certification Mark:



Product:

Personal Fall-Arrest Systems

Brand Name:

MILLER

Model(s):

MB9000 (Full Body Harness)

MB9006 (Single Lanyard with an energy absorber) MB9007 (Twin Lanyards with an energy absorber)

Product Details:

Refer to following page(s)

Standard(s):

SS 528-1:2006 SS 528-2:2006 SS 528-5:2006 SS 528-6:2006

Country of Origin:

People's Republic of China

Test Report(s):

7191134837-EEC16-SHD

Valid until:

2024-07-04

Products listed under Class 1B must have TÜV SÜD PSB PLS mark as shown above affixed/printed on them. Failure to comply with this requirement may result in revocation of this certificate.

Page 1 of 2

Issued on:

2019-07-05

Vice-President (Certification Department) TÜV SÜD PSB

This Certificate is part of a full Report and should be read in conjunction with it. This Certificate remains the property of TÜV SÜD PSB Pte Ltd and shall be returned upon request. The use of this Certificate is subjected to TÜV SÜD Group Testing and Certification Regulations; TÜV SÜD PSB Pte Ltd (PSB) General Terms and Conditions of Business and PSB Product Listing Scheme (PLS) Application Fact Sheet. The manufacturer is solely responsible for compliance of any product that has the same designation as the product type-tested. Persons relying on this Certificate should verify its validity by checking TÜV SÜD PSB's website at www.tuv.sud-psb.sg



CERTIFICATE OF CONFORMITY

No. CLSBN 080538 0025 Rev. 00

Initial No. -

Product Details:

Model	Description
MB9000	Full body harness with dorsal anchorage point and three (3) points buckle Classification: Class A (Back "D" ring for fall arrest purpose) Primary Strap: 43 mm width
MB9006	Single lanyard with an energy absorber (13 mm diameter fibre rope-based lanyard) Type: 2 (used in PFAS where the potential freefall distance limited to a maximum of 4m) Number of Lanyard: One (1) Rope Lanyard: MB9002 Steel Karabiner: MB0006 (20mm gate opening) Steel Snap Hook: MB0005 (54mm gate opening)
MB9007	Twin lanyards with an energy absorber (13 mm diameter fibre rope-based lanyard) Type: 2 (used in PFAS where the potential freefall distance limited to a maximum of 4m) Number of Lanyard: Two (2) Rope Lanyard: MB9002 Steel Karabiner: MB0006 (20mm gate opening) Steel Snap Hook: MB0005 (54mm gate opening)

Page 2 of 2

Issued on: 2019-07-05

Vice-President (Certification Department)
TÜV SÜD PSB

This Certificate is part of a full Report and should be read in conjunction with it. This Certificate remains the property of TÜV SÜD PSB Pte Ltd and shall be returned upon request. The use of this Certificate is subjected to TÜV SÜD Group Testing and Certification Regulations; TÜV SÜD PSB Pte Ltd (PSB) General Terms and Conditions of Business and PSB Product Listing Scheme (PLS) Application Fact Sheet. The manufacturer is solely responsible for compliance of any product that has the same designation as the product type-tested. Persons relying on this Certificate should verify its validity by checking TÜV SÜD PSB's website at www.tuv.sud-psb.sg