



Honeywell Titan™ HD
1Point Harness – H Design®
New Feeling of Safety!

New Feeling of Safety!

FEATURE & BENEFITS:

- Exclusive H Architecture of the harness, thanks to its ergonomically placed webbing, providing a total freedom of movement for the arms.
- Horizontal leg straps preventing uncomfortable friction on the legs and on the groin v/s traditional leg straps increasing comfort for the user during work.

- Easy to access and adjust buckles: Intuitive movement up to down.
- Very accessible anchor points: Bigger Back D-ring for easy Rescue Operations.
- Adjustable chest strap with mating buckles for a perfect fit in height and width.
- Adjustable leg straps with mating buckles.
- Easy front strap clip.

- EN 361 - Safety Harness.

- Fluro - Orange textile, high visible stitching, back fall indicators to facilitate visual inspection before working.
- Sealed labels improving yearly checking follow-up for a better traceability.
- Fall Indicator feature for better and easy visual periodical inspection.

A black and orange striped fall indicator device, likely a personal fall protection system component, shown against a white background. The device consists of a black fabric strap with orange vertical stripes and a yellow label in the center that reads "FALL INDICATOR".



Attach lanyard when not in use to
avoid tripping hazard



Protects the product from UV, dust
and external wear and tear



H Design® Harness								
SKU	Standard	Back D Ring	Fall Indicator	Chest Strap Buckles	Shoulder Strap Buckles	Leg Strap Buckles	Lanyard Hanging Rings	Harness Design
EH10001	EN 361 CE	YES	YES	MATING	MATING	MATING	YES	H Design®
EH10001-L								HON Patented Design

Honeywell Titan™ Shock Absorber

New Feeling of Safety!

Pack-Type Shock-Absorbing Lanyards include the shock-absorber pack as an integral part of a standard lanyard. In the event of a fall, the pack expands, reducing fall forces while a back-up safety strap deploys for added fall protection.



KEY FEATURES

Shock Absorber pack is designed with a specially-woven inner core that smoothly expands reducing fall arrest forces.

Rebar Hook

Auto Lock Galvanized Steel 57mm opening scaffolding hooks with Nikel Plating



Reinforced Webbing Protection

Extra Polyester cover reinforced to ends avoid wear



Polyester Webbing

New Vibrant Hi - Viz 45mm webbing to avoid entanglements



Karabiner Hook

Screw Lock Galvanized Steel 17mm opening karabiner hooks



Shock Absorber

Heated Treated shrink packed transparent cover shock absorber



Product Label

UV Protected Labels which withstands hard environmental conditons



TECHNICAL SPECIFICATIONS

- Working Length: 6 ft.
- Extended Fall Length: 4 ft.
- Weight Capacity: 310 lb.
- Number of Legs: 2
- Line Material: Polyester
- Hardware Material: Steel
- HI-Viz Orange
- Strap Width: 45mm"
- Visual Load Indicator: Yes
- Locking Anchorage Connection Hook Type: Rebar
- Anchorage Hook Gate Opening: 17mm
- Locking Harness Connection Hook Type: Karabiner
- Harness Hook Gate Opening: 57mm
- Tensile Strength: 5000 lb.
- Standards: EN354, EN355, EN362

SIZES		WEIGHT		PACKAGING	
	6 FT (1.8M) Length		1.5Kg		5 PCS/CARTON

Shock Absorbing Lanyard				
SKU	Number of Legs	Harness Connection	Anchorage Connection	Standard Length
EL20001	2	Karabiner Hook	Rebar Hooks	6ft. (1.8m)


Honeywell Titan™ Tool/Carry Bag

New Feeling of Safety!



Carry Handle

High Strength handle with reinforced stitching



Polyester Bag

High Quality polyester bag carries upto 5 kg



Velcro Patch

2 High Quality Velcro patch to support the weight



Tool Bag Handle

2 Tool bag handles attached to the bag for greater strength and stability



ANSAC

ANSAC TECHNOLOGY (S) PTE LTD

35, Marsiling Industrial Estate Road 3,
#02-01 Singapore 739257

T: (65) 6368 0225 F: (65) 6368 8023

E: sales@ansac-tech.com.sg | www.ansac-tech.com.sg

Honeywell Industrial Safety

Honeywell International ME Ltd,
Building 2, Emaar Business Park,
PO Box: 232362, Dubai, UAE

⚠ WARNING! This equipment should only be used after reading and understanding the manufacturer's instructions. Failure to follow instructions could result in serious injury or fatality.

LMBT | 3/16
© 2018 Honeywell International Inc.

Honeywell