



8AL Aluminium Cylinders

Product Offering

Calgaz has two types of 8AL cylinders designed to meet your needs. The 8ALE and 8ALU are both approved for global use and vary only slightly in terms of appearance and weight.

All cylinders have the universal C10 valve as standard and can be filled with both non-reactive and reactive gases.

Characteristic				
	Contents	Pressure	Dimensions	Weight
8ALE	58 litres	35 bar (500 psi)	362 mm x 89 mm (14 1/4" x 3 1/2")	1.2 kg (2.65lb)
8ALU	58 litres	35 bar (500 psi)	362 mm x 89 mm (14 1/4" x 3 1/2")	0.73 kg (1.6 lb)



*8ALU Picture

Specifications				
	Approvals	Type	Cylinder Valve	Recommended Equipment
8ALE	Global	Non-Refillable	C10	Most commonly used regulators include 700 Series, DFR 2000 Series, or 4200 Trigger regulators.
8ALU	Global	Non-Refillable	C10	



Contact Details

Americas

Global Headquarters

Houston, TX, USA
+1 713 624 8000

Customer Service and Manufacturing Facility

Cambridge, MD, USA
+1 800 638 1197

Europe, Middle East & Africa

Customer Service, Sales and Manufacturing Facility

Stoke-on-Trent, United
Kingdom
+44 0808 164 8897

Middle East Sales

Dubai, UAE
+971 56 131 2346

South East Asia & Australia

Customer Service and Distribution

Singapore
+65 3129 2321

China

Customer Service and Distribution

Shanghai
+86 21 6090 3711

info@calgaz.com

www.calgaz.com

Authorised Distributor in Singapore

ANSAC

ANSAC TECHNOLOGY (S) PTE LTD

35, Marsiling Industrial Estate Road 3,
#02-01 Singapore 739257

+65 6368 0225 | sales@ansac-tech.com.sg

www.ansac-tech.com.sg

Contact Us

